

According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

#### Other means of identification:

Not relevant

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Adhesive. For professional users only.

Not for Consumer Use

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

FIX-R

Harding Way

PE27 3YJ St Ives - Cambridgeshire - United Kingdom

Phone: +44 (0) 1480 466 777 sigassured@sigplc.com www.fix-r.co.uk

1.4 Emergency telephone number: +44 (0) 1274 696979 (Monday - Friday 8am - 5pm GMT)

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

# GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Carc. 2: Carcinogenicity, Category 2, H351

Eye Irrit. 2: Eye irritation, Category 2, H319

Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

#### 2.2 Label elements:

## GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

#### Danger





# Hazard statements:

Carc. 2: H351 - Suspected of causing cancer.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 2: HAZARDS IDENTIFICATION (continued)

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing vapours

P264: Wash thoroughly after use.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P284: Wear respiratory protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

#### Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

# Substances that contribute to the classification

Dichloromethane (CAS: 75-09-2); Methylenediphenyl diisocyanate (CAS: 26447-40-5)

#### **Additional Labelling:**

As from 24 August 2023 adequate training is required before industrial or professional use.

#### Additional labeling:

RCH004a Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

RCH004b Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

RCH004c This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

#### 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture of substances

#### Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification Chemical name/Classification			Concentration
CAS:	75-09-2	Dichloromethane Carc. 2: H351; Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H336 - Warning	<u>(1)</u>	30 - <40 %
CAS:		Methylenediphenyl diisocyanate  Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	<b>(!)</b>	1 - <5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:



According to UK REACH (S.I. 2019/758)

#### 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Specific concentration limit
Methylenediphenyl diisocyanate CAS: 26447-40-5	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0.1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Methylenediphenyl diisocyanate	LD50 oral	Not relevant	
CAS: 26447-40-5	LD50 dermal	Not relevant	
	LC50 inhalation	11 mg/L (ATEi)	

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

# By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

# By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

# 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

# Unsuitable extinguishing media:

Non-applicable

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

# 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

#### Additional provisions:

Page 3/14



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

# 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### Other information:

Storage Temperature: 5°C - 25°C

Shelf Life: 12 Months from Date of Manufacture

7.3 Specific end use(s):

See Section 1.2

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- CONTINUED ON NEXT PAGE -

# According to UK REACH (S.I. 2019/758)



# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

Safety data sheet

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### 8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
Dichloromethane (1)	WEL (8h)	100 ppm	353 mg/m³
CAS: 75-09-2	WEL (15 min)	200 ppm	706 mg/m <sup>3</sup>

<sup>(1)</sup> Skin

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVS) - EH40/2005 - Isocyanates (applies to HDI, IPDI, TDI and MDI): 1 µmol isocyanate-derived diamine/mol creatinine in urine. Sampling Time: At the end of the period of exposure.

#### **DNEL (Workers):**

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Dichloromethane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 75-09-2	Dermal	Not relevant	Not relevant	12 mg/kg	Not relevant
EC: 200-838-9	Inhalation	Not relevant	Not relevant	176 mg/m³	Not relevant
Methylenediphenyl diisocyanate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 26447-40-5	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 247-714-0	Inhalation	Not relevant	0.1 mg/m <sup>3</sup>	Not relevant	0.05 mg/m <sup>3</sup>

#### **DNEL** (General population):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Dichloromethane	Oral	Not relevant	Not relevant	0.06 mg/kg	Not relevant
CAS: 75-09-2	Dermal	Not relevant	Not relevant	5.82 mg/kg	Not relevant
EC: 200-838-9	Inhalation	Not relevant	Not relevant	44 mg/m³	Not relevant
Methylenediphenyl diisocyanate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 26447-40-5	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 247-714-0	Inhalation	Not relevant	0.05 mg/m³	Not relevant	0.025 mg/m³

#### PNEC:

Identification				
Dichloromethane	STP	26 mg/L	Fresh water	0.31 mg/L
CAS: 75-09-2	Soil	0.33 mg/kg	Marine water	0.031 mg/L
EC: 200-838-9	Intermittent	0.27 mg/L	Sediment (Fresh water)	2.57 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.26 mg/kg
Methylenediphenyl diisocyanate	STP	1 mg/L	Fresh water	1 mg/L
CAS: 26447-40-5	Soil	1 mg/kg	Marine water	0.1 mg/L
EC: 247-714-0	Intermittent	10 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant

#### 8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding << UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: PVA, Breakthrough time: > 480 min)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions.  Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration.

#### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>-</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

# Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 30 % weight V.O.C. density at 20 °C: Not relevant

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Not available

Odour:

Hydrocarbon

Odour threshold:

Not relevant

Volatility:

Boiling point at atmospheric pressure: ca. 39 - 40 °C

\*Not relevant due to the nature of the product, not providing information property of its hazards.



Not relevant \*



# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Not relevant \* Vapour pressure at 20 °C: Not relevant \* Vapour pressure at 50 °C: Evaporation rate at 20 °C: Not relevant \*

Product description:

Density at 20 °C: Not relevant \*

Relative density at 20 °C: 1.1

Not relevant \* Dynamic viscosity at 20 °C: Not relevant \* Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: >20.5 mm<sup>2</sup>/s Concentration: Not relevant \* pH: Not relevant \* Vapour density at 20 °C: Not relevant \* Partition coefficient n-octanol/water 20 °C: Not relevant \* Solubility in water at 20 °C: Not relevant \* Solubility properties: Not relevant \* Decomposition temperature: Not relevant \*

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Not relevant \* Not relevant \* Autoignition temperature: Not relevant \* Lower flammability limit: Upper flammability limit: Not relevant \*

Particle characteristics:

Melting point/freezing point:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not relevant \* Not relevant \* Oxidising properties: Corrosive to metals: Not relevant \* Not relevant \* Heat of combustion: Aerosols-total percentage (by mass) of flammable Not relevant \*

components:

Other safety characteristics:

Surface tension at 20 °C: Not relevant \* Refraction index: Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

# 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

# 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

Date of compilation: 18/09/2023 Version: 1 Page 7/14



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 10: STABILITY AND REACTIVITY (continued)

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
    - IARC: Dichloromethane (2A)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Not relevant

# Specific toxicology information on the substances:

Identification	Ac	Acute toxicity	
Dichloromethane	LD50 oral	>5000 mg/kg	
CAS: 75-09-2	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	86 mg/L (4 h)	Rat
Methylenediphenyl diisocyanate	LD50 oral	5100 mg/kg	Rat
CAS: 26447-40-5	LD50 dermal	5100 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (ATEi)	

# Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>5000 mg/kg (Calculation method)	Non-applicable
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	224.49 mg/L (4 h) (Calculation method)	0 %

# **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

# 12.1 Toxicity:

# Acute toxicity:

Identification	Concentration		Species	Genus
Dichloromethane	LC50	330 mg/L (96 h)	Pimephales promelas	Fish
CAS: 75-09-2	EC50	270 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	2300 mg/L (3 h)	Chlorella vulgaris	Algae

# Chronic toxicity:

Identification	Concentration		Species	Genus
Dichloromethane	NOEC	357 mg/L	Pimephales promelas	Fish
CAS: 75-09-2	NOEC	Not relevant		

# 12.2 Persistence and degradability:

# Substance-specific information:

Identification	Degradability		Biodegradability	
Dichloromethane	BOD5	Not relevant	Concentration	100 mg/L
CAS: 75-09-2	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	13 %

#### 12.3 Bioaccumulative potential:

# Substance-specific information:

Identification	Bioaccumulation potential		
Dichloromethane	BCF	6	
CAS: 75-09-2	Pow Log	1.25	
	Potential	Low	

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dichloromethane	Koc	24	Henry	329.31 Pa·m³/mol
CAS: 75-09-2	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.877E-2 N/m (25 °C)	Moist soil	Yes



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 12: ECOLOGICAL INFORMATION (continued)

#### Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

#### Other adverse effects:

Not described

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods:

Code	Description	Waste class
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

#### Type of waste:

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP7 Carcinogenic, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

# **SECTION 14: TRANSPORT INFORMATION**

# Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number: UN2810

UN proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (Dichloromethane) 14.2

Transport hazard class(es): 6.1 Labels: 6.1 14.4 Packing group:

14.5 Environmental hazards: No 14.6 Special precautions for user

C/E Tunnel restriction code:

Physico-Chemical properties: see section 9 14.7 Transport in bulk according to Not relevant

Annex II of Marpol and the IBC

Code:

#### Transport of dangerous goods by sea:

With regard to IMDG 41-22:

14.1 **UN** number: UN2810

14.2 UN proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (Dichloromethane)



Transport hazard class(es): 14.3 6.1 Labels: 6 1 14.4 Packing group: ı

14.5 Marine pollutant: Special precautions for user

> Special regulations: 315, 274 EmS Codes: F-A. S-A Physico-Chemical properties: see section 9

Limited quantities:

Segregation group: Not relevant Transport in bulk according to Not relevant

Annex II of Marpol and the IBC

Code:

Date of compilation: 18/09/2023 Version: 1 Page 10/14

Nο

#### Safety data sheet According to UK REACH (S.I. 2019/758)



# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 14: TRANSPORT INFORMATION (continued)

# Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number: UN2810

14.2 UN proper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (Dichloromethane)

Nο

Transport hazard class(es): 14.3 Labels: 6.1 14.4 Packing group: ı 14.5 Environmental hazards:

14.6 Special precautions for user

Physico-Chemical properties: see section 9 Transport in bulk according to Not relevant

Annex II of Marpol and the IBC

Code:

# **SECTION 15: REGULATORY INFORMATION**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:
  - Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
  - Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Not relevant

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):

Date of compilation: 18/09/2023 Version: 1 Page 11/14



According to UK REACH (S.I. 2019/758)

#### 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 15: REGULATORY INFORMATION (continued)

Contains more than 0.1 % of Methylenediphenyl diisocyanate by weight. This product may not be distributed in its present form for first-time sale to the general public after 27th December 2010 unless the packaging contains protective gloves meeting the provisions of Regulation (EU) 2016/425.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays.
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Methylenediphenyl diisocyanate by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

- (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).
- 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:
- (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".
- 3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling disocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks
- 4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:
- (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).
- (b) the training elements in points (a) and (b) of paragraph 5 for the following uses:
- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route
- (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:
- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.
- 5. Training elements:
- (a) general training, including on-line training, on:
- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazardimportance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety
- certification or documented proof that training has been successfully completed



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 15: REGULATORY INFORMATION (continued)

- (b) intermediate level training, including on-line training, on:
- additional behaviour-based aspects
- maintenance
- management of change
- evaluation of existing safety instructions
- risk in relation to application process used
   certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed
- 6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.
- 7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.
- 8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.
- 9. Member States shall include in their reports pursuant to Article 117(1) the following information:
- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
- (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.
- 10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the

# Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this

# Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

# Other information:

Annex XVII restriction Entry 59 Paint Stripper

#### **SECTION 16: OTHER INFORMATION**

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

# Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation.
- H351: Suspected of causing cancer.
- H336: May cause drowsiness or dizziness.
- H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.

# Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):



According to UK REACH (S.I. 2019/758)

# 10649620 - FIX-R EPDM Reinforced Single Ply PU Deck Adhesive 5L

# SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H332 - Harmful if inhaled.

Carc. 2: H351 - Suspected of causing cancer. Eye Irrit. 2: H319 - Causes serious eye irritation.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

Skin Irrit. 2: Calculation method Carc. 2: Calculation method STOT SE 3: Calculation method Resp. Sens. 1: Calculation method Skin Sens. 1: Calculation method Eye Irrit. 2: Calculation method

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

## Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the seccurity requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.