

**10513507, 10524174 - FIX-R Fibred 10 5Kg & 15Kg****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier:** 10513507, 10524174 - FIX-R Fibred 10 5Kg & 15Kg

**Other means of identification:**

Not relevant

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Waterproofing. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

FIX-R  
Harding Way  
PE27 3YJ St Ives - Cambridgeshire - United Kingdom  
Phone: +44 (0) 1480 466 777  
sigassured@sigplc.com  
www.fix-r.co.uk

**1.4 Emergency telephone number:** +44 (0) 1274 696979 (Monday - Friday 8am - 5pm GMT)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

**2.2 Label elements:**

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

**Warning**



**Hazard statements:**

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

**Precautionary statements:**

- CONTINUED ON NEXT PAGE -

## SECTION 2: HAZARDS IDENTIFICATION (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe vapours  
P264: Wash thoroughly after use.  
P280: Wear protective gloves/protective clothing/eye protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314: Get medical advice/attention if you feel unwell.  
P321: Specific treatment is urgently needed (go to see a doctor with the Safety data sheet for this product).  
P332+P313: If skin irritation occurs: Get medical advice/attention.  
P337+P313: If eye irritation persists: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.  
P403+P235: Store in a well-ventilated place. Keep cool.  
P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

### Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

### Substances that contribute to the classification

Reaction mass of ethylbenzene and m-xylene and p-xylene

### 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:


Non-applicable

### 3.2 Mixture:

**Chemical description:** Mixture of substances

### Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Non-applicable	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b> Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	10 - <20 % 

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	Not relevant	
Reaction mass of ethylbenzene and m-xylene and p-xylene	LD50 oral	Not relevant	
CAS: Non-applicable	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (ATEI)	

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

- CONTINUED ON NEXT PAGE -

#### SECTION 4: FIRST AID MEASURES (continued)

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

#### SECTION 5: FIREFIGHTING MEASURES

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

It is recommended to avoid environmental spillage of both the product and its container.

**6.3 Methods and material for containment and cleaning up:**

- CONTINUED ON NEXT PAGE -

## SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

#### B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

#### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

#### A.- Specific storage requirements

Store in a cool, dry, well-ventilated location

#### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

See Section 1.2

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
	WEL (8h)	WEL (15 min)	WEL (8h)
Di- <i>isobutyl</i> phthalate CAS: 28553-12-0			5 mg/m <sup>3</sup>
Titanium dioxide (aerodynamic diameter ≥ 10 µm) CAS: 13463-67-7			4 mg/m <sup>3</sup>
Carbon black CAS: 1333-86-4			3.5 mg/m <sup>3</sup>
			7 mg/m <sup>3</sup>

#### Biological limit values:

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVs) - EH40/2005

Identification	NULL	NULL	NULL
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	1030 mg/g (NULL)	Methyl hippuric acid in urine	Post shift

- CONTINUED ON NEXT PAGE -

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Not relevant	Not relevant	12.5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65.3 mg/m <sup>3</sup>	65.3 mg/m <sup>3</sup>

**PNEC:**

Identification				
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	STP	6.58 mg/L	Fresh water	0.327 mg/L
	Soil	2.31 mg/kg	Marine water	0.327 mg/L
	Intermittent	0.327 mg/L	Sediment (Fresh water)	12.46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12.46 mg/kg

**8.2 Exposure controls:**


**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**


The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

**C.- Specific protection for the hands**


Pictogram	PPE	Remarks
 Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.


**D.- Eye and face protection**

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.



**E.- Body protection**

Pictogram	PPE	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Remarks
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:**

V.O.C. (Supply): 10 % weight  
V.O.C. density at 20 °C: 147 kg/m<sup>3</sup> (147 g/L)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C: Liquid  
Appearance: Not available  
Colour: Not available  
Odour: Characteristic  
Odour threshold: Not relevant \*

**Volatility:**

Boiling point at atmospheric pressure: Not relevant \*  
Vapour pressure at 20 °C: Not relevant \*  
Vapour pressure at 50 °C: Not relevant \*  
Evaporation rate at 20 °C: Not relevant \*

**Product description:**

Density at 20 °C: ca. 1400 - 1500 kg/m<sup>3</sup>  
Relative density at 20 °C: Not relevant \*  
Dynamic viscosity at 20 °C: ca. 3000 - 6000 cP  
Kinematic viscosity at 20 °C: >20.5 mm<sup>2</sup>/s  
Kinematic viscosity at 40 °C: Not relevant \*  
Concentration: Not relevant \*  
pH: Not relevant \*  
Vapour density at 20 °C: Not relevant \*  
Partition coefficient n-octanol/water 20 °C: Not relevant \*  
Solubility in water at 20 °C: Not relevant \*  
Solubility properties: Not relevant \*  
Decomposition temperature: Not relevant \*  
Melting point/freezing point: Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

**Flammability:**

Flash Point:	42 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	Not relevant *
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

**Other safety characteristics:**

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- CONTINUED ON NEXT PAGE -

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**A- Ingestion (acute effect):**

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Carbon black (2B); M-Tolyldiene Diisocyanate(<0.1 % O=C=N-R-N=C=O) (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Organs affected: All gross lesions and masses.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Reaction mass of ethylbenzene and m-xylene and p-xylene	2100 mg/kg	1100 mg/kg (ATEi)	Rat
CAS: Non-applicable	LC50 inhalation	11 mg/L (ATEi)	

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	21000 mg/kg (Calculation method)	Non-applicable
Dermal	11000 mg/kg (Calculation method)	0 %
Inhalation	110 mg/L (4 h) (Calculation method)	0 %

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -



## SECTION 12: ECOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

### 12.1 Toxicity:

#### Acute toxicity:

Identification	Concentration		Species	Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae

#### Chronic toxicity:

Identification	Concentration		Species	Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	NOEC	1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1.17 mg/L	Ceriodaphnia dubia	Crustacean

### 12.2 Persistence and degradability:

#### Substance-specific information:

Identification	Degradability		Biodegradability	
	Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BOD5	Not relevant	Concentration
COD		Not relevant	Period	28 days
BOD5/COD		Not relevant	% Biodegradable	88 %

### 12.3 Bioaccumulative potential:

#### Substance-specific information:

Identification	Bioaccumulation potential	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BCF	9
	Pow Log	2.77
	Potential	Low

### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	Koc	202	Henry
Conclusion		Moderate	Dry soil	Yes
Surface tension		Not relevant	Moist soil	Yes

### 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

#### Type of waste:

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

- CONTINUED ON NEXT PAGE -

## SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
**Labels:** 3  
**14.4 Packing group:** I  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Tunnel restriction code: D/E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 500 mL  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Not relevant

### Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
**Labels:** 3  
**14.4 Packing group:** I  
**14.5 Marine pollutant:** No  
**14.6 Special precautions for user**  
 Special regulations: 367, 163  
 EmS Codes: F-E, S-E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 500 mL  
 Segregation group: Not relevant  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Not relevant

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
**Labels:** 3  
**14.4 Packing group:** I  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Not relevant

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

#### The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):

- CONTINUED ON NEXT PAGE -

## SECTION 15: REGULATORY INFORMATION (continued)

Contains Di-isononyl phthalate. 1. Shall not be used as substances or in mixtures, in concentrations greater than 0,1 % by weight of the plasticised material, in toys and childcare articles which can be placed in the mouth by children. 2. Such toys and childcare articles containing these phthalates in a concentration greater than 0,1 % by weight of the plasticised material shall not be placed on the market. 4. For the purpose of this entry 'childcare article' shall mean any product intended to facilitate sleep, relaxation, hygiene, the feeding of children or sucking on the part of children.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.  
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.  
Control of Substances Hazardous to Health Regulations 2002 (as amended)  
EH40/2005 Workplace exposure limits.

## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.  
H373: May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.  
H226: Flammable liquid and vapour.  
H319: Causes serious eye irritation.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Skin Irrit. 2: H315 - Causes skin irritation.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT SE 3: H335 - May cause respiratory irritation.

### Classification procedure:

Skin Irrit. 2: Calculation method  
STOT RE 2: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)  
Eye Irrit. 2: Calculation method

### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

### Abbreviations and acronyms:



PITCHED AND FLAT ROOFING SOLUTIONS

## Safety data sheet

According to UK REACH (S.I. 2019/758)

**10513507, 10524174 - FIX-R Fibred 10 5Kg & 15Kg**

### SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -