

# FIX-R SBS Torch On Cap Sheet Green/Brown/Black/BlueGrey

**DoP Reference:** FIX-R SBS Torch On Cap Sheet Green-Brown-Black-BlueGrey UK CA DOP V1 August 2022

**1. UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:** 10205567 / 10205568 / 10205569 / 10205570

**2. TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**

Product Code	Reference Code	Nominal Dimensions	Colour	Nominal Weight kg/m <sup>2</sup>
10205567	SG100622	1m x 8m	Green	4.525
10205568	SG100626	1m x 8m	Brown	4.525
10205569	SG100624	1m x 8m	Black	4.525
10205570	SG100623	1m x 8m	Blue/Grey	4.525

**3. INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT, IN ACCORDANCE WITH THE APPLICABLE DESIGNATED TECHNICAL SPECIFICATION**

Flexible sheets for waterproofing — Reinforced bitumen sheets for roof waterproofing

**4. NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**

FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ

**5. NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**

N/A

**6. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**

2+

**7. NAME AND IDENTIFICATION NUMBER OF THE NOTIFIED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A DESIGNATED STANDARD**

0086 BSI Insurance UK Ltd

**8. NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**

N/A

**9. DECLARED PERFORMANCE ACCORDING TO:** EN 13707:2004+A2:2009


Characteristics	Result	Units	Tolerance	Ref. Norm
External fire performance (Note 1)	NPD	-	-	EN 13707:2004+A2:2009
Reaction to fire	NPD	-	-	
Watertightness ≤ 60kPa	Pass	-	-	
Tensile force length	450	N/50mm	± 20%	
Tensile force width	300	N/50mm	± 20%	
Elongation length	20	%	± 1	
Elongation width	30	%	± 1	
Root resistant	NPD	-	-	
Resistance to static loading: method A	NPD	Kg	-	
Resistance to impact: method A	NPD	Mm	-	
Resistance to tearing length	NPD	N	-0;-	
Resistance to tearing width	NPD	N	-0;-	
Peel resistance to joints initial: length/width	NPD	N/50 mm	-0;-	
Shear resistance of joints: initial	NPD	N/50 mm	-0;-	
Pliability initial (up/under)	≤ 10	°C	-	
Durability: pliability after heat oven exposure	NPD	°C	± 5°C	
Danger Substances (Note 2)				

NPD = No Performance Declared

**Note 1:** Since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone.

**Note 2:** In absence of test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of FIX-R, SIG Trading Ltd:

**Steve Marr - SIG UK Compliance Director**  
SIG Trading Ltd, Sheffield - 22/08/22