



FIX-R Undercloak Soffit Strip

DoP Reference: FIX-R Undercloak Soffit Board CE DOP V2 Nov 2022


- UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:** Undercloak Soffit Board
- TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**
See product label for more information
- INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT, IN ACCORDANCE WITH THE APPLICABLE HARMONISED TECHNICAL SPECIFICATION**
Fibre-cement flat sheet for use as external wall and ceiling finishes non structural
- NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**
FIX-R, Harding Way, St Ives, Cambridgeshire, PE27 3YJ
- NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**
MIT International Trade S.L., Ctra. Sarria a Vallvidrera, 259 local 08017, Barcelona, Spain T: + 34 93 406 98 85
- SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**
4
- NAME AND IDENTIFICATION NUMBER OF THE NOTIFIED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A HARMONISED STANDARD**
N/A
- NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**
N/A
- DECLARED PERFORMANCE ACCORDING TO:** EN 12467:2012+A2:2018

Essential Characteristics	Performance / Result	Harmonised Technical Specification
Dimensional Tolerance - Length/Width - Straightness - Squareness - Thickness	L1 L1 L1 Non-Textured (+/-10%)	EN 12467:2012+A2:2018
Supplied Nominal Thickness (mm)	3.2 & 4.5	EN 12467:2012+A2:2018
Mechanical Resistance - Bending Strength (MOR)	Category A, Class 2	EN 12467:2012+A2:2018
Reaction to Fire	A1	EN 13501-1:2018
Release of Dangerous Substances	NPD	EN 12467:2012+A2:2018
Water Impermeability	Pass	EN 12467:2012+A2:2018
Water Vapour Permeability	Not Applicable	EN 12467:2012+A2:2018
Durability Against Warm Water	$R_1 \geq 0.75$	EN 12467:2012+A2:2018
Durability Against Soak/Dry	$R_1 \geq 0.75$	EN 12467:2012+A2:2018
Durability Against Freeze Thaw	$R_1 \geq 0.75$	EN 12467:2012+A2:2018
Durability Against Heat-Rain	$R_1 \geq 0.75$	EN 12467:2012+A2:2018
Density (g/cm ³)	1.34	EN 12467:2012+A2:2018
All Other Essential Characteristics Not Identified Above	NPD	

NPD = No Performance Declared

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of FIX-R, SIG Trading Ltd:



Steve Marr - SIG UK Compliance Director
SIG Trading Ltd, Sheffield - 30/11/22